



Nominal pressure		1.6MPa					
Test pressure	Shell test	2.4	Mpa	Test medium	Water	Test temperature	Normal temperature
	Seal test	1.76			Air		
	Gas seal test	0.6					
Applicable medium		Water, Oil, Gas					
Applicable temperature		-29~425°C					

NOTE:

- 1.Design and Manufacture for valve according to GB/T 12235-2007.
- 2.Face-to-face dimensions for valve according to GB/T 12221-2005.
- 3.End flange dimensions for valve according to JB/T 79.1-1994.
- 4.Inspection and Test for valve according to GB/T 13927-2008.

	L	d	D	A
DN15	17.5	15	51	46
DN20	20	20	61	56
DN25	23	25	70	65
DN32	28	32	79	74
DN40	31.5	40	88	84
DN50	40	50	108	102
DN65	46	65	125	121
DN80	50	80	135	131
DN100	60	100	161	156
DN125	90	125	196	190
DN150	106	150	228	220
DN200	140	196	270	/
DN250	146	246	328	/

4	BONNET	1	A351 CF8M
3	SPRING	1	SS316
2	DISC	1	A351 CF8M
1	BODY	1	A351 CF8M
NO.	DESCRIPTION	QTY	AT512A
			MATERIAL
GENERAL DRAWING			SCREWED END SWING CHECK VALVE
MARK	BEFORE MODIFIED	AFTER MODIFIED	
DRA.		APP.	
CHK.		DATE	
			SCALE
			AT512A