



	L	d	BSPP/BSPT/NPT	W	H
DN15	55	14	1/2	70	92
DN20	60	20	3/4	70	101
DN25	68	25	1	80	113
DN32	76	32	1 1/4	80	133
DN40	80	40	1 1/2	100	153
DN50	93	50	2	100	171
DN65	118	63	2 1/2	140	205
DN80	137	72	3	140	226

		Nominal pressure		200psi			
Test pressure	Shell test	2.1	Mpa	Test medium	Water	Test temperature	Normal temperature
	Seal test	1.6			Air		
	Gas seal test	0.6					
Applicable medium		Water, Oil, Gas					
Applicable temperature		-29~180°C					

13	NUT	1	A194 8	A194 8M
12	SPRING WASHER	1	SS304	SS304
11	HANDWHEEL	1	ZINC ALLOY	ZINC ALLOY
10	BONNET NUT	1	A351 CF8	A351 CF8
9	GLAND	1	SS304	SS304
8	PACKING	1	RPTFE	RPTFE
7	BONNET	1	A351 CF8	A351 CF8M
6	WASHER	1	A240 304	A240 316
5	RING	1	A240 304	A240 316
4	GASKET	1	RPTFE	RPTFE
3	STEM	1	A276 304	A276 316
2	DISC	1	A351 CF8	A351 CF8M
1	BODY	1	A351 CF8	A351 CF8M

NO.	DESCRIPTION	QTY	MATERIAL	
			A6GA1	A6GA2
			GENERAL DRAWING	
			SCREWED END GATE VALVE	
MARK	BEFORE MODIFIED	AFTER MODIFIED	DATE	
DRA.		APP.		SCALE
CHK.		DATE		
			A6GA1/GA2	