



	L	d	BSP/BSPT/NPT	W	H	H1
DN15	65	14	1/2	70	86	94
DN20	75	20	3/4	70	92	100
DN25	90	24	1	80	103	117
DN32	105	31	1 1/4	100	122	138
DN40	120	38	1 1/2	100	130	148
DN50	140	49	2	100	150	175
DN65	152	60	2 1/2	120	200	229
DN80	175	75	3	140	222	256

		Nominal pressure		200psi			
Test pressure	Shell test	2.1	Mpa	Test medium	Water	Test temperature	
	Seal test	1.6			Air		Normal temperature
	Gas seal test	0.6					
Applicable medium		Water,Oil,Gas					
Applicable temperature		-29~180°C					

12	NUT		A194 8	A194 8M
11	SPRING WASHER		SS304	SS304
10	HANDWHEEL		ZINC ALLOY	ZINC ALLOY
9	BONNET NUT		A351 CF8	A351 CF8
8	GLAND		SS304	SS304
7	PACKING	1	RPTFE	RPTFE
6	WASHER	1	A240 304	A240 316
5	BONNET	1	A351 CF8	A351 CF8M
4	GASKET	1	RPTFE	RPTFE
3	STEM	1	A276 304	A276 316
2	DISC	1	A351 CF8	A351 CF8M
1	BODY	1	A351 CF8	A351 CF8M

NO.	DESCRIPTION	QTY	MATERIAL	
			A6GL 1	A6GL 2
GENERAL DRAWING			SCREWED END GLOBE VALVE	
MARK	BEFORE MODIFIED	AFTER MODIFIED	DATE	
DRA.		APP.		SCALE
CHK.		DATE		
				A6GL 1/GL 2