



	L	d	BSPP/BSPT/NPT	H
DN15	65	15	1/2	41.5
DN20	75	20	3/4	46
DN25	90	25	1	54
DN32	105	32	1 1/4	58
DN40	120	38	1 1/2	66.5
DN50	140	50	2	74
DN65	165	64	2 1/2	89
DN80	185	76	3	102.5

Nominal pressure			200Psi				
Test pressure	Shell test	2.1	Mpa	Test medium	Water	Test temperature	Normal temperature
	Seal test	1.6			Air		
	Gas seal test	0.6					
Applicable medium			Water, Oil, Gas				
Applicable temperature			-29-180°C				

NOTE:

- 1.Design and Manufacture for valve according to ASME B16.34.
- 2.Inspection and Test for valve according to API 598.
- 3.The connection of screwed for valve according to ISO 7/1 or ANSI B1.20.1.

7	WASHER	1	RPTFE
6	HEXAGON HEAD BOLT	1	A193 B8
5	BONNET	1	A351 CF8
4	GASKET	1	RPTFE
3	DOWEL	1	A276 304
2	DISC	1	A351 CF8
1	BODY	1	A351 CF8

NO.	DESCRIPTION	QTY	A6SC1	
			MATERIAL	
			GENERAL DRAWING	
			SCREWED END SWING CHECK VALVE	
			A6SC1	

MARK	BEFORE MODIFIED	AFTER MODIFIED	DATE
DRA.		APP.	
CHK.		DATE	

SCALE